

# → GUILLOTINE IDEAL 4215

## CONVENIENT, ELECTRIC GUILLOTINE WITH 430 MM CUTTING LENGTH OR FORMATS UP TO A3

! "SCS" - the Safety Cutting System made by IDEAL provides numerous safety features: hinged, electronically controlled safety guard on the front table; transparent safety cover on the rear table; main switch and safety lock with key; electronically controlled true two-hand operation; 24 volt control (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade changing device with covered cutting edge; blade depth adjustment from the outside of the machine; easy blade change from the front of the machine without removing covers; cutting stick can be turned or replaced easily from the outside of the machine | 430 mm cutting length | cuts up to 500 sheets of paper (70 g/m<sup>2</sup>) or bound brochures up to 40 mm | high quality blade made from "Solingen steel" | solid steel blade carrier | adjustable blade guides made of hardened steel | patented fast flick action clamp | precision side lay | spindle guided backgauge with hand crank | digital measurement readout for backgauge positioning (mm or inches) | optical cutting line with bright and durable LEDs | solid all-metal construction | designed as table top machine, a stand or a cabinet are available as option

Power supply: 230 V / 50 Hz / 1~<sup>1</sup>, Motor performance (input capacity): 0.45 kW

Dimensions (H x W x D): 360/1055<sup>2</sup>/1080<sup>3</sup> x 640 x 695 mm,

Weight: 80/90<sup>2</sup>/112<sup>3</sup> kg, Colour: pearl grey

<sup>1</sup> other voltages available

<sup>2</sup> with stand

<sup>3</sup> with cabinet



IDEAL 4215  
with cabinet as option



L.T.E. Listed 802 D

### SAFETY GUARDS



Transparent safety guards made from unbreakable Lexan<sup>®</sup> on front and rear table: The hinged front safety guard locks in the lower position while cutting.

### DIGITAL DISPLAY



Precise backgauge positioning with the hand crank is very easy due to the digital measurement readout, which can be switched over from mm to inch.

### SAFETY FIRST



The numerous features of "SCS" (Safety Cutting System) include a main switch, a true two-hand operation as well as an electric lock with key.

### → IDEAL 4215

Cutting length	430 mm
Cutting height	40 mm
Narrow cut	35 mm
Table depth	390 mm
Digital display	mm/inches